

Apex 7000 is the solution to your validator needs.

# APEX 7000

## **Under the Hood**

Configurable DIP switches, automatic self-calibration, along with all the accessories and options that you need to get the job done. Quality, Confidence, Value; the Apex 7000 is the bill validator of choice for today's automatic equipment operator.

Operating Voltage: 12 VDC standard, 120 VAC or 24 VAC supply optional.

Operating Current: 180mA idle; 500mA operating; 1.50 stalled.

Operating Temp: 0C to 60C, 90% non-condensing humidity.

Acceptance Rate: Greater than 95% (including second-time insertion of rejected bill).

Acceptance Speed: Approx. 20 bills per minute.


Sensor Array: (8) Optical Sensors; Optional Magnetic head.


Net Weight:

Stackered: 2.3 lbs. / 1.04 kg.

Warranty:

2 years, parts and labor.





**Reliability** – over 10 years in the field and counting, the Apex 7000 is the benchmark for stability and resilience.

**Flexibility** – Simple DIP switch and PC configuration.

- Flash updateable.
- Bills up to 72 mm wide accepted.
- Automatic self-calibration; no user calibration required.
- 12VDC standard or optional 120VAC internal power supply.
- Stackerless version available.

**Security** - The highest security against fraudulent bills.

- Dual-stage optical anti-stringing technology.

Multiple interfaces available (see below).

Simple DIP switch and PC Configuration Dual Stage Optical AntiStringing Easy to Update High security against counterfeits Simple on-board diagnostics Accepts bills up to 72mm wide Automatic self-calibration Stackerless version available

### Model Number Selection

Apex - 7XOO - X X X - XXX

#### Model

74 - No Mag. Head 76 - With Mag. Head

#### **Bezel Options**

00 – Standard Bezel 01 – "Coinco" Style Bezel 02 – "VFM" Style Bezel

#### Type

U – Upstacker

D – Downstacker

S - Stackerless

#### Cashbox

N - None (Stackerless)

A – Non-Locking, 200 Note Plastic Cassette

C - 500 Bill Non-Locking Plastic Cassette

D - Lockable 500 Note Plastic Cassette

7 – 700 Bill Cassette

1 – 1000 Bill Cassette

#### Power Supply / Communications

1 - 12 VDC / RS232 Optional

3 - 120 VAC supply

4 - MDB Option

6 - IGT IDO22

9 - 24 VAC

#### Country Code

ISO 3-character country code Example: USA for United States







